



PROGTECH
Lighting


SAFETY BAR SUPER HP EVO

SAFETY BAR SUPER HP EVO je industrijska LED svetiljka namenjena bezbednosnom osvetljenju mostnih dizalica koje rade na velikim visinama i u veoma osvetljenim okruženjima. Idealna je za povećanje bezbednosti rukovaoca dizalicom i radnika u okolnim zonama kretanja, naročito u bučnim i opasnim radnim uslovima.

Kada se montira na mostnu dizalicu, SAFETY BAR SUPER HP EVO emituje snop plave, crvene, zelene ili žute svetlosti ka tlu, pružajući vizuelno upozorenje na dolazak dizalice i označavajući zonu kretanja ispred i iza nje. Uređaj se napaja naponom od 230 V AC. SAFETY BAR SUPER HP EVO odlikuju visoko efikasne LED diode i fokusirana optika.

čineći projekciju veoma uočljivom.

Uređaj poseduje integrisani ventilator radi optimizacije odvođenja toplote. Korišćeni materijali – poput eloksiranog aluminijuma i nerđajućeg čelika – čine SAFETY BAR SUPER HP EVO visokokvalitetnim i izdržljivim proizvodom.



SAFETY BAR SUPER HP EVO is the LED industrial lamp designed for safety lighting of industrial cranes mounted at elevated heights and in bright environments, ideal to increase the safety of the crane operator and general workers in the surrounding areas, especially in loud environments.

SAFETY BAR SUPER HP EVO has LEDs with high efficiency and a concentrating optic; this allows the beam being very visible on the ground.

The projector has an integrated fan for a better heat dissipation.

The materials used, such as anodized aluminium and stainless steel, make the SAFETY BAR SUPER HP EVO a durable and high quality product.

**5 YEARS
WARRANTY**

Made in Italy



KOD/ CODING	SAFETY BAR SUPER HP BLUE LC0285N	SAFETY BAR SUPER HP RED LC0286N	SAFETY BAR SUPER HP GREEN LC0371N	SAFETY BAR SUPER HP YELLOW LC0372N
NAPAJANJE POWER SUPPLY	90-305Vac / 50-60Hz			
MAKSIMALNA POTROŠNJA ENERGIJE MAXIMUM POWER INPUT	98W	80W	98W	
IZVOR SOURCE	n° 4 HIGH POWER PLAVA LED	n° 4 HIGH POWER CRVENA LED	n° 4 HIGH POWER ZELENA LED	n° 4 HIGH POWER ZELENA LED (sa Žutim filterom)
PROJEKTOVANA FORMA PROJECTED FIGURE	BAR			
DOMINANTNA TALASNA DUŽINA DOMINANT WAVELENGTH	460nm (Plava)	620nm (Crvena)	525nm (Zelena)	580nm (Žuta)
RADNA TEMPERATURA OPERATING TEMPERATURE	Da/OD -40°C a/DO +60°C	Da/OD -40°C a/DO +50°C	Da/OD -40°C a/DO+60°C	
KONTROLA CONTROL	On/Off			
MATERIJALI MATERIALS	· Ekstrudirani eloksirani aluminijum (konstrukcija) · Obojeni čelik (nosači) · Nerđajući čelik (šrafovi i kablovske uvodnice) · Staklo (sočiva) · EPDM (zaptivke) / EPDM (zaptivke)			
STEPEN IP ZAŠTITE IP PROTECTION CLASS	IP65			
OCENA OTPORNOSTI NA UDAR IK IK IMPACT RESISTANCE RATING	IK08			
KLASA FOTOBIOLOŠKOG RIZIKA PHOTOBIOLOGICAL SAFETY RISK GROUP	RG1 (za rastojanja veća od 10,61 m; za kraća rastojanja, RG2) (za rastojanja veća od 10,61 m; za manja rastojanja, RG2)	RG1		
TEŽINA WEIGHT	4,2 Kg			
DIMENZIJE PAKOVANJA PACKAGING DIMENSIONS	300 mm (L) x 285 mm (W) x 230 mm (H) 2 lampe po kutiji / 2 lampas each box			
DIMENZIJE LAMPE LAMP DIMENSION	260 mm (L) x 240 mm (W) x 65 mm (H)			



PROGTECH srl

Headquarter:
Via Campagnola, 40
24126 Bergamo

Production & Warehouse:
Via Lombardia, 9
24040 Bonate Sopra (BG)



T. +39.035.0388117



info@progtech.it
www.progtech.it