



PROGTECH
Lighting


SAFETY BAR HP EVO

SAFETY BAR HP EVO je industrijska LED svetiljka namenjena bezbednosnom osvetljenju mostnih dizalica; idealna je za povećanje bezbednosti rukovalaca i radnika u okolnim radnim zonama, naročito u bučnim ili opasnim okruženjima.

Kada se montira na mostnu dizalicu, SAFETY BAR HP EVO emituje snop svetlosti (plave, crvene, zelene ili žute boje) na pod, pružajući vizuelno upozorenje na približavanje dizalice i obeležavajući radnu zonu ispred i iza nje.

Uređaj radi na napajanju od 230 V AC. SAFETY BAR HP EVO odlikuju LED diode visoke efikasnosti i sočivo sa optikom za fokusiranje svetlosti.

Uređaj sadrži integrirani ventilator radi optimizacije odvođenja toplote.



Korišćeni materijali, kao što su eloksirani aluminijum i nerđajući čelik, čine SAFETY BAR HP EVO visokokvalitetnim i izdržljivim proizvodom.



SAFETY BAR HP EVO is the LED industrial lamp designed for safety lighting of industrial cranes, ideal to increase the safety of the crane operator and general workers in the surrounding areas, especially in loud environments. SAFETY BAR HP EVO, applied on the crane, emits a blue, red, green or yellow light beam on the ground that can visually warn about the arrival of the crane by identifying the front and rear manoeuvring areas.

The unit is powered at 230 Vac. SAFETY BAR HP EVO is made with high efficiency LEDs and lens with concentrating optic.

The projector has an integrated fan for a better heat dissipation.

The materials used, such as anodized aluminium and stainless steel, make the SAFETY BAR HP EVO a durable and high quality product.

**5 YEARS
WARRANTY**

Made in Italy



KOD / CODING	SAFETY BAR HP EVO BLUE LC0117N	SAFETY BAR HP EVO RED LC0118N	SAFETY BAR HP EVO GREEN LC0119N	SAFETY BAR HP EVO YELLOW LC0539N
NAPAJANJE POWER SUPPLY	90-305Vac / 50-60Hz			
MAKSIMALNA POTROŠNJA ENERGIJE MAXIMUM POWER INPUT	65W	50W	65W	
IZVOR SOURCE	n° 3 HIGH POWER PLAVA LED	n° 3 HIGH POWER CRVENA LED	n° 3 HIGH POWER ZELENA LED	n° 3 HIGH POWER ZELENA LED (sa ŽUTIM filterom)
PROJEKTOVANA FORMA PROJECTED FIGURE	BAR			
DOMINANTNA TALASNA DUŽINA DOMINANT WAVELENGTH	460nm (Plava)	620nm (Crvena)	525nm (Zelena)	580nm (Žuta)
RADNA TEMPERATURA OPERATING TEMPERATURE	Da/OD -40°C a/DO +60°C	Da/OD -40°C a/DO+50°C	Da/OD -40°C a/DO +60°C	
KONTROLA CONTROL	On/Off			
MATERIJALI MATERIALS	• Ekstrudirani eloksirani aluminijum (konstrukcija) • Obojeni čelik (nosači) • Nerđajući čelik (šrafovi i kablovske uvodnice) / Nerđajući čelik (šrafovi i kablovske uvodnice) • Staklo (sočiva) • EPDM (zaptivke) / EPDM (zaptivke) • PVC (zatvaranje sočiva)			
STEPEN IP ZAŠTITE IP PROTECTION CLASS	IP65			
STEPEN OTPORNOSTI NA UDARCE IK PROTECTION CLASS	IK08			
KLASA FOTOBIOLOŠKOG RIZIKA PHOTOBIOLOGICAL SAFETY RISK GROUP	RG1			
TEŽINA WEIGHT	4,2 Kg			
DIMENZIJE PAKOVANJA PACKAGING DIMENSIONS	300 mm (L) x 285 mm (W) x 230 mm (H) 2 lampe po kutiji / 2 lamps each box			
DIMENZIJE LAMPE LAMP DIMENSION	260 mm (L) x 240 mm (W) x 65 mm (H)			



PROGTECH srl

Headquarter:
Via Campagnola, 40
24126 Bergamo

Production & Warehouse:
Via Lombardia, 9
24040 Bonate Sopra (BG)



T. +39.035.0388117



info@progtech.it
www.progtech.it